


PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 6: C07C 17/20, 19/08	A1	(11) International Publication Number: WO 99/25670 (43) International Publication Date: 27 May 1999 (27.05.99)
(21) International Application Number: PCT/US98/24661 (22) International Filing Date: 18 November 1998 (18.11.98) (30) Priority Data: 08/972,531 18 November 1997 (18.11.97) US (71) Applicant: ALLIEDSIGNAL INC. [US/US]; 101 Columbia Road, P.O. Box 2245, Morristown, NJ 07962-2245 (US). (72) Inventors: CERRI, Gustavo; 3 Pine Tree Place, Parsippany, NJ 07054 (US). HUNT, Maurice, William; 109 West Mantua Avenue, Wenonah, NJ 08090 (US). KEELER, David, W.; 5 Wilkeshire Boulevard, Randolph, NJ 07869 (US). YOUNG, Frank, P.; 77 Cherryville Station Road, Flemington, NJ 08822 (US). (74) Agents: CRISS, Roger, H. et al.; AlliedSignal Inc., Law Dept. (R. Fels), 101 Columbia Road, P.O. Box 2245, Morristown, NJ 07962-2245 (US).	(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, GH, GM, HU, ID, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, UZ, VN, YU, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG). Published <i>With international search report. Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</i>	

(54) Title: PROCESS FOR THE PREPARATION OF DIFLUOROMETHANE**(57) Abstract**

A liquid phase fluorination process for producing difluoromethane without corrosion is provided. In the process of this invention, methylene chloride and hydrogen fluoride are reacted in a reactor made of fluorinated polymer to produce a reaction product while a heated recycle stream of process reactants is fed into the reactor.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece			TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
RJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	NZ	New Zealand		
CM	Cameroun			PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakhstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LJ	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

PROCESS FOR THE PREPARATION OF DIFLUOROMETHANE

Field of the Invention

- 5 The present invention relates to a hydrofluorination process. In particular, this invention provides a liquid phase hydrofluorination process for producing difluoromethane that exhibits efficient heat transfer and high productivity and that eliminates corrosion in the reactor system.

Background of the Invention

- 10 Liquid phase fluorination processes using antimony pentachloride catalysts to produce chlorofluorocarbons ("CFC's") and hydrochlorofluorocarbons ("HCFC's") are well known. CFC's and HCFC's have been implicated in the depletion of the earth's ozone layer and, thus, a need has developed for processes
- 15 for the production of hydrofluorocarbons ("HFC's"), which are believed not to deplete the ozone layer. One HFC of particular interest is difluoromethane ("HFC-32"). Known liquid phase processes for producing HFC-32 using antimony pentachloride catalysts are very corrosive of the materials of construction used in the process. Therefore, a need exists for a liquid phase fluorination process for
- 20 producing HFC's that overcomes this problem.

Brief Description of the Drawings

Fig. 1 is a schematic diagram illustrating one embodiment of the process of the invention.

- 25 Fig. 2 is a schematic diagram illustrating another embodiment of the process of the invention.

Description of the Invention and the Preferred Embodiments

It has been discovered that a liquid phase fluorination process for producing HFC's without corrosion, but that maintains high productivity and efficient heat transfer may be carried out by heating a recycle of process reactants. The process of this invention comprises, consists essentially of, and consists of
5 reacting methylene chloride ("HCC-30") and hydrogen fluoride in a reactor made of fluorinated polymer to produce a reaction product and feeding concurrently a heated recycle stream of process reactants into the reactor.

For purposes of the invention, by "process reactants" is meant at least one
10 of hydrogen fluoride, HCC-30, monochloromonofluoromethane ("HCFC-31"), and catalyst. Also, for purposes of this invention, by "made of a fluorinated polymer" means that the reactor is constructed of a fluorinated polymer, the reactor is a metal shell lined with a fluorinated polymer, or the reactor is a metal shell lined with a first layer that is a fluorinated polymer and a second layer that is made of
15 carbon bricks or rings, such as graphite, KARBATE®, and the like. Suitable metals for the reactor metal shell may be any of the conventional materials of construction including, without limitation, carbon steel, stainless steel, INCONEL 600®, INCOLOY 825®, MONEL®, and HASTELLOY®.

Suitable fluorinated polymers useful in the reactor will be apparent to those
20 ordinarily skilled in the art. Illustrative polymers include, without limitation, polytetrafluoroethylene polymer, perfluoroalkoxy polymer, ethylene tetrafluoroethylene polymer, vinylidene fluoride polymer, ethylene hexafluoropropylene polymer and the like. Preferably, polytetrafluoroethylene
25 polymer is used.

The liquid phase fluorination reaction preferably takes place in the presence of an effective amount of any suitable fluorination catalyst. Suitable fluorination catalysts include, without limitation, antimony halide catalysts as well as

molybdenum, titanium, tantalum, tin, niobium, and iron catalysts. The invention may find its greatest utility with antimony pentachloride catalyst. The catalyst may be treated prior to use by any known pretreatment method. The amount of catalyst used is an amount effective to catalyze the fluorination of the HCC-30.

5

Suitable corrosion resistant equipment is used in carrying out the process of the invention. In the process, the HCC-30 and hydrogen fluoride are reacted in a reactor made of fluorinated polymer. The fresh hydrogen fluoride is vaporized and superheated, prior to being fed into the reactor, to a temperature such that the hydrogen fluoride is superheated above its saturation point. Preferably, the fresh hydrogen fluoride is fed into the reactor through an eductor or sparger to promote mixing within the reactor. Reaction temperatures may be from about 70 to about 110° C, preferably from about 75-95° C. The reactor temperature and pressure are maintained such that at least a portion of the hydrogen fluoride in the reactor is maintained in the liquid state.

15

Reacting the HCC-30 and hydrogen fluoride in the presence of the catalyst produces a reaction product that is a vapor mixture containing the desired product, reaction intermediates, unreacted starting materials and catalyst. The vapor is sent to a distillation column, or other convenient apparatus, for separation. The bottom section and piping connecting the distillation column with the reactor preferably are made of fluorinated polymer. The column bottoms stream, containing the process reactants is recycled back to the reactor. Additionally, a portion of the reactor liquid may be taken from the reactor, vaporized and superheated, and then returned to the reactor at a temperature of less than about 350° F, preferably less than about 250° F.

20

25

In all embodiments, the recycle stream of process reactants is heated, meaning that the recycle stream is returned to the reactor at a temperature effective

to maintain a reactor temperature sufficient to produce enough vapor and liquid flow in the first distillation column to effect the separation desired. One ordinarily skilled in the art will be able to readily determine the temperature to which to heat the process reactants by a consideration of the temperature desired to be maintained in the reactor and the amount of vapor needed to be generated so that the first distillation column may effect an efficient separation. Generally, the temperature of the process reactants recycle stream fed into the reactor is between about 100 and about 200 °C, preferably about 130 and about 180 °C.

In one embodiment, fresh hydrogen fluoride, fresh HCC-30, and a recycle stream containing mainly hydrogen fluoride, HCFC-31, and HCC-30, is fed to a reactor made of fluorinated polymer. The fresh hydrogen fluoride and the recycle stream are vaporized and superheated, together or separately, to a temperature required to maintain the reaction mixture in the reactor at the desired reaction temperature. The vaporizer and super heater may be combined into a single heat exchanger. The superheated vapors are introduced into the reactor by any convenient means, preferably through a sparger, such as a perforated pipe or through an eductor to promote mixing and heat transfer into the reactor. The fresh HCC-30 preferably is not heated prior to feeding it into the reactor.

The reactor is connected by a pipe to a first distillation column and, through this pipe, the liquid reflux from the bottom of the column, the column bottoms, is sent back to the reactor through the same pipe or through a second pipe. The distillation column is equipped with a condenser supplied with any convenient means of cooling to produce the reflux. From the top of the column, the column overhead which is the crude product is withdrawn. The column overhead from this column contains hydrogen chloride, HFC-32, HCFC-31, HCC-30, and hydrogen fluoride. This overhead is fed into a second distillation column to separate the HFC-32 and hydrogen chloride in the column overhead to be sent

for further purification. The remaining material, containing hydrogen fluoride, HCFC-31, and HCC-30, is withdrawn from the bottom of the second distillation column and recycled to the reactor after vaporizing and superheating as described.

5 In another embodiment, the overhead of the first distillation column is fed into a second column to separate the hydrogen chloride as the second column overhead. The remaining material, hydrogen fluoride, HFC-32, HCFC-31, and HCC-30, is withdrawn as the column bottoms and fed into a third distillation column. In the third column, HFC-32 product is separated as the overhead and
10 sent for further purification. The bottoms of the column is recycled to the reactor after vaporizing and superheating.

The invention will be clarified further by the following non-limiting examples.

15

Examples

Example 1

An apparatus arranged as shown in Fig. 1 is used to produce HFC-32. Referring to Fig. 1, fresh hydrogen fluoride is vaporized in heat exchanger V-1 and
20 superheated in super heater H-1 to about 175° C. The superheated hydrogen fluoride is fed along with liquid HCC-30, stream 2, into reactor R-1, which reactor contains antimony pentachloride catalyst and operates at a temperature of about 90° C and a pressure of between 100 - 300 psig, the pressure maintained so as to keep some of the hydrogen fluoride in the reactor as a liquid.

25

The vapor generated from the reaction mixture, containing hydrogen chloride, HFC-32, HCFC-31 and HCC-30 and hydrogen fluoride as well as entrained catalyst is sent through a pipe lined with PTFE to the bottom of distillation column T-1, located above reactor R-1 and equipped with an overhead

condenser to produce the liquid reflux. The heat input to the column is provided by the heat contained in the inlet streams to reactor R-1. T-1 is made of fluorinated polymer as are the trays or packing. The liquid from the bottoms of T-1, containing all of the entrained catalyst, and a part of the HCC-30 and hydrogen fluoride, flows back to the reactor by gravity through a pipe made of a fluorinated polymer. The T-1 overhead, containing HFC-32 and hydrogen chloride and part of the HCFC-31 along with HCC-30 and hydrogen fluoride is sent to a second distillation column T-2.

10 The T-2 heat input is provided by a column reboiler. In T-2, the HFC-32 and hydrogen chloride are separated in the overhead stream and sent for further processing. The T-2 bottoms, containing HCFC-31, HCC-30, and hydrogen fluoride is sent back to reactor R-1 through vaporizer V-2 and superheater H-2. The heat input in both H-2 and V-2 is such that it supplies the heating requirements to maintain the reaction temperature and produces enough vapor and liquid traffic
15 in T-1 to effect the desired separation in T-1. The temperature in the example is about 175° C. The process results in the production of HFC-32 with no corrosion and with increased heat transfer.

20 Example 2

An apparatus arranged as shown in Fig. 2 is used to produce HFC-32. Referring to Fig. 2, hydrogen fluoride is vaporized in heat exchanger V-1 and superheated in superheater H-1 to about 175° C. The superheated hydrogen fluoride is fed along with HCC-30, and into reactor R-1, which reactor contains
25 antimony pentachloride catalyst and operates at a temperature of about 90° C and a pressure of about 100-300 psig, so as to keep some of the hydrogen fluoride in Reactor R-1 in the liquid state.

Vapor from reactor R-1, containing hydrogen chloride, HFC-32, HCFC-31, HCC-30, hydrogen fluoride and entrained catalyst is sent to T-1, a first distillation column which is configured and outfitted as in Example 1. The bottoms from column T-1, containing HCC-30 and hydrogen fluoride are sent back to reactor R-1 as in Example 1. The T-1 overhead, containing HFC-32, hydrogen chloride, HCFC-31, HCC-30 and hydrogen fluoride is sent to a second column, T-2.

T-2 separates the hydrogen chloride as the column overhead and the bottoms stream, containing HFC-32, HCFC-31, HCC-30 and hydrogen fluoride is fed to a third distillation column T-3. Heat input to columns T-2 and T-3 is supplied by column reboilers. T-3 is operated at a higher pressure than reactor R-1 and separates HFC-32 in the overhead stream. The T-3 bottoms stream, containing HCFC-31, HCC-30, and hydrogen fluoride is sent to reactor R-1 through combined vaporizer and superheater H-2 at a temperature sufficient to supply the heating requirements to maintain reaction temperature and produce enough vapor in T-1 to effect the desired separation.

What is claimed is:

1. A process comprising the steps of:
 - (a.) reacting methylene chloride and hydrogen fluoride in a reactor made
 - 5 of a fluorinated polymer to produce a reaction product; and
 - (b) feeding concurrently a heated recycle stream of process reactants into the reactor.
2. The process of claim 1 wherein the reacting of methylene chloride and
- 10 hydrogen fluoride is carried out in the presence of an effective amount of a fluorination catalyst.
3. The process of claim 1 wherein the process reactants recycle stream is heated to a temperature of about 100 to about 200 ° C.
- 15 4. The process of claim 1 wherein the process reactants recycle stream is fed into the reactor through a sparger or an eductor.
5. The process of claim 1 wherein step (b) comprises the steps of:
 - 20 (i) distilling the reaction product in a first distillation column to produce a first column bottoms product that is recycled to the reactor and a first column overhead product comprising hydrogen chloride, difluoromethane, monochloromonofluoromethane, methylene chloride, and hydrogen fluoride;
 - (ii) distilling the first column overhead in a second distillation column
 - 25 to separate a mixture comprising difluoromethane and hydrogen chloride as a second column overhead from a second column bottoms product comprising monochloromonofluoromethane, methylene chloride, and hydrogen fluoride;
 - (iii) vaporizing and superheating the second column bottoms product;
 - and

(iv) recycling the vaporized and superheated second column bottoms product to the reactor.

6. The process of claim 1 wherein step (b) comprises the steps of:

- 5 (i) distilling the reaction product in a first distillation column to produce a first column bottoms product that is recycled to the reactor and a first column overhead product comprising hydrogen chloride, difluoromethane, monochloromonofluoromethane, methylene chloride, and hydrogen fluoride;
- 10 (ii) distilling the first column overhead in a second distillation column to separate hydrogen chloride as a second column overhead from a second column bottoms product comprising difluoromethane, monochloromonofluoromethane, methylene chloride, and hydrogen fluoride;
- 15 (iii) distilling the second column bottoms product in a third distillation column to separate difluoromethane as a third column overhead from a third column bottoms product comprising monochloromonofluoromethane, methylene chloride, and hydrogen fluoride;
- (iv) vaporizing and superheating the third column bottoms product; and
- (v) recycling the vaporized and superheated third column bottoms product to the reactor.

20

7. A process comprising the steps of:

- (a.) reacting methylene chloride and hydrogen fluoride in the presence of an effective amount of a fluorination catalyst and in a reactor made of a fluorinated polymer to produce a reaction product; and
- 25 (b.) distilling the reaction product in a first distillation column to produce a first column bottoms product that is recycled to the reactor and a first column overhead product comprising hydrogen chloride, difluoromethane, monochloromonofluoromethane, methylene chloride, and hydrogen fluoride;

- (c.) distilling the first column overhead in a second distillation column to separate a mixture comprising difluoromethane and hydrogen chloride as a second column overhead from a second column bottoms product comprising monochloromonofluoromethane, methylene chloride, and hydrogen fluoride;
- 5 (d.) vaporizing and superheating the second column bottoms product; and
- (e.) recycling the vaporized and superheated second column bottoms product to the reactor.
- 10 8. The process of claim 7 wherein the first and second column bottoms streams are heated before being recycled to the reactor to a temperature of about 100 to about 200° C.
9. A process comprising the steps of:
- 15 (a.) reacting methylene chloride and hydrogen fluoride in the presence of an effective amount of a fluorination catalyst and in a reactor made of a fluorinated polymer to produce a reaction product; and
- (b.) distilling the reaction product in a first distillation column to produce a first column bottoms product that is recycled to the reactor and a first
- 20 column overhead product comprising hydrogen chloride, difluoromethane, monochloromonofluoromethane, methylene chloride, and hydrogen fluoride;
- (c.) distilling the first column overhead in a second distillation column to separate hydrogen chloride as a second column overhead from a second column bottoms product comprising difluoromethane, monochloromonofluoromethane,
- 25 methylene chloride, and hydrogen fluoride;
- (d.) distilling the second column bottoms product in a third distillation column to separate difluoromethane as a third column overhead from a third column bottoms product comprising monochloromonofluoromethane, methylene chloride, and hydrogen fluoride;

- (e.) vaporizing and superheating the third column bottoms product; and
 - (f) recycling the vaporized and superheated third column bottoms product to the reactor.
- 5 10. The process of claim 9 wherein the first, second, and third column bottoms streams recycled to the reactor are heated to a temperature of about 100 to about 200° C.

FIGURE 1





FIGURE 2



INTERNATIONAL SEARCH REPORT

International Application No
PCT/US 98/24661

A. CLASSIFICATION OF SUBJECT MATTER		
IPC 6 C07C17/20 C07C19/08		
According to International Patent Classification (IPC) or to both national classification and IPC		
B. FIELDS SEARCHED		
Minimum documentation searched (classification system followed by classification symbols)		
IPC 6 C07C		
Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched		
Electronic data base consulted during the international search (name of data base and, where practical, search terms used)		
C. DOCUMENTS CONSIDERED TO BE RELEVANT		
Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	EP 0 805 136 A (ATOCHAM ELF SA) 5 November 1997 see column 6, line 48 - line 51; claim 1; figure 1	1-10
X	WO 97 11043 A (ALLIED SIGNAL INC) 27 March 1997 see page 3, line 11 - line 13; claim 1	1-10
A	EP 0 767 158 A (DAIKIN IND LTD) 9 April 1997 see page 3, line 35; claim 7	1-10
A	US 5 495 057 A (NAM KYUNG H ET AL) 27 February 1996 see figure 1	1-10
<input type="checkbox"/> Further documents are listed in the continuation of box C. <input checked="" type="checkbox"/> Patent family members are listed in annex.		
* Special categories of cited documents : "A" document defining the general state of the art which is not considered to be of particular relevance "E" earlier document but published on or after the international filing date "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified) "O" document referring to an oral disclosure, use, exhibition or other means "P" document published prior to the international filing date but later than the priority date claimed "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art "S" document member of the same patent family		
Date of the actual completion of the international search		Date of mailing of the international search report
8 March 1999		15/03/1999
Name and mailing address of the ISA European Patent Office, P.B. 5818 Patentlaan 2 NL - 2250 HW Rijswijk Tel. (+31-70) 340-2040; Tx. 31 651 epo nl; Fax: (+31-70) 340-3016		Authorized officer Janus, S

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No
PCT/US 98/24661

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
EP 0805136 A	05-11-1997	FR 2748022 A	31-10-1997
		AU 1913397 A	06-11-1997
		CA 2203434 A	29-10-1997
		CN 1172097 A	04-02-1998
		JP 10053544 A	24-02-1998
WO 9711043 A	27-03-1997	US 5763708 A	09-06-1998
		AU 6977596 A	09-04-1997
		CA 2232596 A	27-03-1997
		CN 1201446 A	09-12-1998
		EP 0854848 A	29-07-1998
EP 0767158 A	09-04-1997	PL 325554 A	03-08-1998
		AU 697434 B	08-10-1998
		AU 2629195 A	15-01-1996
		BR 9508062 A	12-08-1997
		US 5744659 A	28-04-1998
US 5495057 A	27-02-1996	CA 2193634 A	28-12-1995
		CN 1168660 A	24-12-1997
		WO 9535271 A	28-12-1995
		FR 2728895 A	05-07-1996
		JP 2840929 B	24-12-1998
		JP 8183748 A	16-07-1996